

Surface mounting thermostats with housing GAT



- Mechanical temperature controller
- Ideal for underfloor heating systems
- Temperature limitation at pipes
- Easy installation with strap

Application Surface mounting thermostat for strap mounting at pipes from 16 to 100 mm diameter. The version with internal adjustment and temperature control range up to 60 °C is specially suited for underfloor heating systems.

Description The surface mounting thermostat uses a bimetal strip (element consisting of two metal strips with different heat expansion coefficients). When the temperature changes, the bimetal strip bends which triggers electrical switching.

Technical specifications

Type
GAT

Operating range
20/60 °C and 20/90 °C

Tolerance
+2 K / -8 K

Switching differential
 $\Delta T 8 \pm 3 K$

Adjustment
GAT/7RC: Externally adjustable
GAT/7HC: Internally adjustable

Probe element
Bimetal

Operating temperature range
Housing: Max. 85 °C

Housing

Upper part: Plastic (PVC), grey (RAL 7035)
Base plate: Galvanised sheet steel

Cable entry

Plastic (PVC), grey (RAL 7040)
M 20 x 1.5

Degree of protection housing

IP 20 (EN 60529)

Response time

1 K/minute

Electrical switching contact

Changeover contact

Contact rating


NC 16 (2.5) A 250 V AC
NO 2.5 A 250 V AC

- Options**
- Safety surface mounting thermostat with housing and with manual reset type GSA/TCS (liquid filled)


Surface mounting thermostats with housing GAT

Housing types and dimensions (mm)


GAT/7RC, external adjustment








GAT/7HC, internal adjustment



Switching scheme



Thermostats with housing

DG: G, PG: 4	Adjustment	Operating range/ switching point	Capillary length	Stem length	Type	Part no.	Price €
Surface mounting thermostats with housing							
	External	20/60 °C	---	---	GAT/7RC	67400X	
	External	20/90 °C	---	---	GAT/7RC	67401X	
	Internal	20/60 °C	---	---	GAT/7HC	67402X	
	Internal	20/90 °C	---	---	GAT/7HC	67403X	
	Internal	30/70 °C	---	---	GSA/9SC	67404X	
Immersion thermostats with housing							
	External	0/90 °C	---	100 mm	GTT/7RG	67407X	
	External	0/90 °C	---	150 mm	GTT/7RG	67408AX	
	External	0/90 °C	---	200 mm	GTT/7RG	67408BX	
	Internal	0/90 °C	---	100 mm	GTT/7HG	67413X	
	Internal	0/90 °C	---	150 mm	GTT/7HG	67414AX	
	Internal	0/90 °C	---	200 mm	GTT/7HG	67414BX	
	Fixed	100 °C	---	100 mm	GST/9SG	67417X	
Capillary type thermostats with housing/room thermostats with housing							
	External	0/90 °C	1,000 mm	---	GTK/7RD	67421X	
	External	0/90 °C	2,000 mm	---	GTK/7RD	67424X	
	Internal	70/110 °C	1,500 mm	---	GSK/9SF	67418	
	External	0/40 °C	---	---	GRT/7RT	67464X	
	External	0/55 °C	---	---	GRT/7RT	67465X	
	Internal	0/40 °C	---	---	GRT/7HT	67466X	
	Internal	0/55 °C	---	---	GRT/7HT	67467X	
Twin thermostats with housing							
	Internal/ external	0/90 °C – 30/120 °C	---	100 mm	GDT/8HR	67447X	
	Fixed/external	0/90 °C (100 °C)	---	100 mm	GDT/8RS	67453X	
	Fixed/external	0/90 °C (100 °C)	---	150 mm	GDT/8RS	67454AX	
	Fixed/external	0/90 °C (100 °C)	---	200 mm	GDT/8RS	67454BX	

* Minimum order quantity for non-stock items = 100 pieces.